

	Lubricant Selection for	
	small calibers	medium and large calibers
Anchor plates, Anchor wheel teeth, Inhibition	Oil Type 1-3*, LGN Watch Oil, Oil Gyrosynth 99214 (TS5310)	Oil Type 3-5* Oil Clock 859
Balance Bearing, Shock protection	Oil Type 1-3*, LGN Watch Oil, Oil Gyrosynth 99214 (TS5310)	Oil Type 3-5* Oil Clock 859
High-speed oscillator	Oil Silber K7132 hv(TS1130)	
Grain storage	Oil Type 1-3*, LGN Watch Oil, Oil Gyrosynth 99214 (TS5310)	
Gear pin Bearings	Oil Type 1-3*, LGN Watch Oil, Oil Gyrosynth 99214 (TS5310)	Oil Type 3-5* Oil Clock 859
Stone storage	Oil Type 1-3*, LGN Watch Oil, Oil Gyrosynth 99214 (TS5310)	Oil Type 1-3*, LGN Watch Oil, Oil Gyrosynth 99214 (TS5310)
Ball bearing	Oil Gyrosynth 99214 (TS5310)	Oil Gyrosynth 99214 (TS5310)
Plastic bearing	Oil K2363/100 Plastic Grease 11741+PTFE	Oil K2363/509 blue (Ts2302) Plastic Grease K2363
Anchor shaft		Precision Oil 12764* Precision Oil 12767*
Winding Parts, Pointer Parts, Winding wheels, Lever	Precision Grease B52* Fluid Grease Gyrosynth 99214-8 LGN Watch Grease	Precision Grease R27* Precision Grease 12765-4* Fluid Grease Clock 859-8
Driving spring, Spring housing, Spring cores	Oil Type 1-3*, LGN Watch Oil, Oil Clock 992 (TS5200), Oil Gyrosynth 99214 (TS5310)	Precision Grease R27* Fluid Grease Clock 859-8 Precision Grease Clock 859 PTFE Graphitol-Oil* (TK1360)
Automatic drag spings	Precision Grease B52* Watch Grease Clock 859-8+PTFE LGN Watch Grease	
Tower clocks	Tower Clock Oil TK1310, Precision Grease R27*, Oil Silber K 7132 lv, PTFE-Grease K 7132	
Special Oil	Emergency Clock Oil TS5900: Special Oil to make Resinous Bearings Working	
Remarks:	Recommendation on epilamization the watch parts with Antispread E2/50 FE60 * semi-synthetic formulations (Service intervals 4 - 6 years)	